



# Radiodetection

Bicotest

power and communications

## T625 TDR

high specification cable fault locator



- The T625 is Bicotest's most advanced TDR cable tester. With a range of 0 to 20 kilometres - it out-performs any other TDR.
- Suitable for any type of metallic cable, including AC live in conjunction with a T600 AC blocking filter
- Superb long distance and short range fault-finding capability is achieved with a 20 V output signal, with pulse width automatically adjusted to suit the selected range.
- Accurate to 0.5 metres in short range mode.
- Dynamic range exceeds anything similar. Fault identification is crystal clear - even at the 20 kilometre limit of its operating range.
- Large, uncluttered full-screen trace display for clarity.
- Eight test modes give fast fault location whether testing a single pair or comparing two pairs, one pair against any of the twelve memories, or crosstalk between two pairs.
- The T625 can measure in metres, feet or time. Dielectric can be set using propagation velocity, cable velocity or cable velocity over 2, (V/2). On-board cable library assists fast, efficient selection.
- Fast function configuration. Dedicated keys for Cursor, Dielectric, Range, Trace Position, Pulse

Amplitude and other most frequently used functions.

- HELP facility provides explanation of controls, contains sample waveforms and allows instrument to be programmed for most common cable types, giving real help to both inexperienced and expert users.
- PC compatibility, via X600 TRACEability Software System, ensures waveforms can be analysed, stored and reloaded to the TDR for on-site, dynamic comparison of the waveforms.
- Bicotest instruments are the ultimate in durability, essential in a true field-portable instrument. Bicotest is the industry standard, proven over 50 years. Comprehensive features and functions, including the high-impact-resistant screen, are tested to destruction. Fit for purpose in any climatic condition, the T625 is supplied in a Bicotest-tough, all-weather shoulder bag.

AS CLOSE AS YOU CAN GET TO FAULTLESS CABLE PERFORMANCE

## Specifications

### T625

RANGES :	0-24 m to 0-20 km in 11 ranges with zoom facility (except on lowest range) (PVF 0.67)	
ACCURACY :	± 0.24% of range at 20 kms	
RESOLUTION :	± 0.1% of range at 20 kms	
PROPAGATION VELOCITY :	PVF :	0.300 to 0.999
	V :	90 to 300 m/μs
	V/2 :	45 to 150 m/μs
GAIN :	0-84 dB max, selectable in 6dB steps Maximum sensitivity 4 mV full scale	
PULSE CHARACTERISTICS :	Amplitude :	Nominally 20 V into 100 Ohms
	Width :	24 ns to 2.25 μs selected with range
	Output Impedance :	100 Ohms
	Balance Control :	0 to 220 Ohms
OUTPUT :	Sockets :	2 pairs 4 mm Banana
	Protection :	300 V rms, 0-60 Hz
DISPLAY :	Type :	High resolution LCD with backlighting (switchable)
	Cursor :	Solid vertical line
	Marker Cursor :	Dotted vertical line
MODES :	Real time :	Line 1, Line 2, Line 1 and Line 2 (dual), Line 1 minus Line 2 (differential), X-Talk (locates crosstalk on telephone cables)
	Memory :	Displays one of 12 memory locations; Line 1 and Memory (dual), Line 1 minus Memory (differential), Memory only
MEMORY :	12 locations that retain information until overwritten	
INTERFACE :	RS 232C to printer or PC	
POWER :	Internal Ni-Cad Batteries - 12 hours operation. (Auto Power-Off 5 mins after last key operation). Ext AC Adaptor, 120 V or 230 V available. Ext DC, 12 V to 20 V operating; 15 V to 20 V charging.	
ENVIRONMENTAL :	Operating Temperature :	-5°C to +50°C
	Storage :	-20°C to +65°C
	Humidity :	93% at +40°C
WATER INGRESS :	IP54	
SAFETY :	IEC 1010	
SIZE (mm) :	75 x 183 x 300 mm inc handle	
WEIGHT (kg) :	2.9 kg inc battery	
DELIVERY INCLUDES :	Weatherproof Shoulder Bag, 8 rechargeable NiCad cells, 2 x 2 m Test Leads, AC Adaptor, DC Plug, Operating Manual.	
ORDERING DETAILS :	T625 Option A :	230 V ± 10%, UK Plug
	T625 Option B :	120 V ± 10%, USA Plug
	T625 Option C :	230 V ± 10%, Euro Plug
OPTIONAL ACCESSORIES :	X600 TRACEability	IBM-Windows compatible PC Interface Software, inc 3.5" disc, operating manual and cable
	T600FS	Single AC Blocking Filter for use on live AC power cables
	T600FD	Dual AC Blocking Filter for use on live AC power cables
WARRANTY:	1 year (2nd year available as an option)	



## Key features

- **Widest range in a hand-portable cable fault locator - from 24 metres to 20 kilometres**
- **Easy to operate**
- **Suitable for any type of metallic cable, including live AC in conjunction with a T600 blocking filter**
- **Large, clear waveform display of full trace for accurate diagnosis**
- **All faults clearly identified - from open circuits to wet joints**
- **Zoom for detailed examination**
- **12 memories for on-site waveform storage and comparison**
- **Measures metres, feet or time**
- **Auto programming for fast configuration**
- **Full PC compatibility for in-depth fault analysis**
- **8 test modes for fast fault location**
- **Dual input enables pair comparison and crosstalk location**
- **Comprehensive training and support services**

Whilst every care is taken that the information contained in this publication is correct, no legal responsibility can be accepted for any inaccuracy. The company reserves the right to alter or modify the information contained herein at any time.  
© Radiodetection Ltd. 2007 All rights reserved.



Radiodetection Ltd. Western Drive, Bristol. BS14 0AF United Kingdom  
Tel: +44 (0) 117 976 7776 Fax: +44 (0) 117 976 7775 E-mail: sales.uk@radiodetection.spx.com

Radiodetection. 154 Portland Road, Bridgton, ME 04009 USA  
Tel: (207) 647-9495 Toll Free: (877) 247-3797 Fax: (207) 647-9496  
E-mail: bridgton@radiodetection.spx.com